

AUTOMATIC BOOM BARRIER IDT PRO 6



RFID



IP 54



Magnetic
Loop Detector
(Optional)



Traffic
Light
(Optional)



5 Million
Cycles



Photocell
(optional)

FEATURES

- Wheel Manual Release. In case of power Off, rotate the wheel manual release on the bottom of the motor to raise the boom manually. When power On, the motor will work normally.
- Machine core with strong and double springs, make the machine core works more steadily.
- Die-Casting alluminium alloy motor, precise and good at thermal radiation.
- Crank and rod structure makes the boom run placidly.
- Reversing on obstacle.
- Auto-Closing.
- Support the infrared photocell for anti-bumping function (optional).
- Support Loop Detector (Optional).
- R&G Light interface (AC 220V, can support lamp with 40W).
- Wire control (switch signal) / Remote control
- Digital limit, more precise.
- Open Close control interface for parking system.
- Provide limit state signal to parking system.

TECHNICAL SPECIFICATION

Model	IDT PRO 6
Running Speed	6 sec
Boom Length	6 m
Boom Type	Telescopic / 2 Way Fence / Folding
Input Voltage	AC 220V \pm 10%
Boom Dimension	45mm x 100mm
Housing Dimension	335mm x 285mm x 925 mm
Frequency	50/60 Hz
Power Consumption	200 W
Humidity	10% RH - 90 % RH
Working Temperature	-35°C ~+60°C
Enclosure Rating	IP 54
MTBF	5 Million Cycles
Traffic Flow Application	500 times/24 hours
Duty Cycle	100%
Net Weight	60 Kg

ORDER INFORMATION

Part No.	IDT.ABB.AC.PRO.6
----------	------------------

APPLICATION AREA



Residential



Health
Care



Educational
Institute



Government



Defense



Hotel



Manufacturing



ID TECH SOLUTIONS PVT. LTD.

610, Udyog Vihar Phase-5, Gurgaon, Haryana - 122016, INDIA | T. : +91-124 - 4255530 (6 Lines)

E.: info@idsolutionsindia.com | W: www.idsolutionsindia.com

The product specifications and descriptions listed in the specification sheet are subject to change anytime without notice.

©2023 ID Tech Solutions Pvt. Ltd. All Rights Reserved.

