

RFID UHF Portable Scanner IDT RHC71

Designed using Impinj R2000 module



Bluetooth 4.0

BLE



IP 54







UHF REID





(Impinj R2000)



IDT RHC71 is a compact lightweight device powered with enterprise-class UHF RFID scanning technology. It is very easy to use and cost-effective. The unique power optimization algorithm delivers the superior battery cycle times that ensure a full shift of power even with intensive usage. Its circular antenna gives a reading range of 3m and its powerful processor makes it the best choice for use in Retail, Construction, ETC, Manufacturing, Transport, Supply Chain Management.

PHYSICAL PARAMETERS

DEDEODMANCE

Dimensions	164.2 x 78.8 x 17.0 mm	
Weight	288g	
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported	
Display	5.2" IPS FHD 1920 x 1080	
Interface	USB 2.0 Type-C, OTG, TypeC headphones supported	
Battery	5000 mAh	
Alarm	Audio & Visual	
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multi-functional key	
Sensor	Gravity Sensor, Light Sensor, Proximity Sensor, Vibration Motor	

PERFORMANCE		
Processor	Cortex-A53 Octa-core 2.5 GHz	
Bluetooth	3GB + 32GB / 4GB + 64GB	
Memory	Supports up to 128 GB Micro SD card	

CAMERA	
Rear Camera	13 MP autofocus rear camera with flash
Front Camera	Optional 5 MP front camera



ENVIRONMENTAL SPECIFICATIONS

Temperature	-40°C to +50°C (Operating), -40°C to +50°C (Storage)	
Humidity	5% RH - 95% RH non condensing	
Sealing	P 65 / IP 67 per IEC sealing specifications	
Drop Test	1.8 m drops to the concrete	

COMMUNICATION

Bluetooth	Bluetooth v2.1+EDR,3.0+HS,v4.1+HS
WWAN	2G, 3G & 4G
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

UHF RFID

Frequency	865-868 MHz EPC C1 GEN2 / ISO18000-6C	
Antenna	Circular polarization (1 dBi)	
Power	0.4 W (26 dBm, +16 dBm to +26 dBm adjustable)	
R/W Range	Up to 3m	
Reading Range	> 200 tags/Sec	

HF (OPTIONAL)

Frequency	13.56 MHz ISO14443A/B, ISO15693
Range	3-8 cm

OPTIONAL FEATURE

Barcode	1D & 2D
Fingerprint	Capacitive TCS1/TCS2; Optical Morpho CBM-E3
InfraRed	38 kHz
PSAM	2 Slots for PSAM Cards with ISO 7816 T=0 7 T=1
IRIS	< 150ms

ACCESSORIES

AC	Adaptor.	USB	Cable.	Lanyard.

Cradle, Holster

ETC

ORDER INFORMATION

Part Number

Standard Optional

IDT.RH.C71

APPLICATION AREA



Retail



Construction



aim

Manufacturing

Unit



Transport



Chain



ID TECH SOLUTIONS PVT. LTD.

610, Udyog Vihar Phase-5, Gurgaon, Haryana - 122016, INDIA | T. : +91-124 - 4255530 (6 Lines) E.: info@idsolutionsindia.com | W: www.idsolutionsindia.com

