

Bluetooth RAIN RFID Reader IDT RHB500 Atex Certified









UHF







Bluetooth 4.0 BLE

h 4.0 Small Form Factor

Atex

IP 65

The IDT RHB500 is an intrinsically safe handheld RAIN RFID Reader, designed for use in hazardous areas and harsh environments such as offshore, marine, chemical and industrial environments. The device is certified for use in ATEX and IECEx Zones 1, 2, 21 and 22. It has been created to work seamlessly with smartphones, tablets, and other Windows/Android devices to give a greater range of functionality. The IDT RHB500 is invaluable for supporting operations such as Inventory Management, Tracking & Tracing, Maintenance Planning and Regulatory Compliance. Lightweight and ergonomic, is easy to use with one hand. The stylus nib means you can even operate a connected tablet whilst wearing gloves, avoiding unnecessary time wasting and helping you work more productively.

PERFORMANCE

| Frequency Range | 865 - 868 MHz 902 - 928 Mhz |
|------------------------|---|
| RF Power | Programmable in 14 levels from 5 dBm ERP (3mW ERP) to 22 dBm ERP (150mW ERP) |
| Antenna | Integrated Linear (horizontal) |
| Standard Compliance | EPC C1 G2 / ISO18000-6C |
| Read Range | Up to 90 cm / Tag Dependant |
| Bluetooth | Class 2 Bluetooth 2.1 + EDR, 10m range |
| Memory | Capacity 48K – 4096 EPC Codes |
| User Interface | Button #1: ON/OFF Button #2: Trigger Led #1: Power Indication and Battery Status (green: High; Red:Low) Led #2: Communication Activity (blue: Bluetooth; Orange: USB) Buzzer: Bi tonal for events signalling Vibration: For events signalling Display: LCD Alphanumeric (8 chars x 2 lines) |
| OS Compatibility | Windows, Android, HID Profile and SPP, Virtual Com Port |
| Battery Life Operating | > 12h with 40'000 tag readings; Standby: > 15 days |
| Battery Charging Time | 2h (typical) |
| | |

IP Rating IP 65

Dimensions (W)59 x (L)128 x (H)22 mm3

-20°C to +55°C **Operating Temperature**

Weight 150 g

FEATURES

Form Factor Small, lightweight and ergonomic

Power Battery

Display LCD

Feedback Vibration / Buzzer

Zone 1 and 2 **Safe Zone**

Certification Ex II 1 GD, Ex ia IIC T4 Ga, Ex ia IIIC T135 Da

Ex I M1 Ex ia I Ma (Hazardous Area Version Only)

US&Canada MET Class I, II, III Div 1, Groups A-G

ORDER INFORMATION

Part Number IDT.RH.B500

APPLICATION AREA



Oil & Gas





Marine

Energy



Asset Tracking



Chemical



Offshore

















