

# **RFID UHF Portable Scanner**

# IDT RHC61

















**UHF** 







Android 11

4G

Fi

Bluetooth Barcode

9

NF(

mera IP 65

IDT RHCP61 is rugged new generation reader with integrated RFID UHF Antenna. It is built with Impini E710/R2000 chip for high accuracy, speedy and long range reading capacity. The ultra-powerful processor, integrated NFC reader and larger capacity battery boost task speed. The integrated long-range antenna delivers best-in-class RFID read range and higher throughput, so inventory counts can be accomplished more

integrated NFC reader and larger capacity battery boost task speed. The integrated long-range antenna delivers best-in-class RFID read range and higher throughput, so inventory counts can be accomplished more quickly and accurately. Its sturdy design and ease of operation makes it a best choice for Retail, Logistics, Inventory, Manufacturing etc.

#### PHYSICAL PARAMETERS

Dimension	202.0 x 72.5 x 32.0 mm
Weight	738 g
Touch Panel	Multi-touch panel, gloves and wet hands supported
Display	4-inch high definition display, 800 X 480
Battery	6700 mAh removable main battery. Built in 100mAh backup battery, supporting battery hot swap
Alarm	Sound, LED Indicator, Vibrator
Card Slot	1 slot for Micro SIM card, 1 slot for TF card
Audio	2 microphones, 1 for noise cancellation; 2 speakers, receiver
Keypad	27 keys / 37 keys / 47 keys; Side keys: 2 SCAN keys + 2 volume keys + 1 user-defined key
Sensor	Accelerometer sensor, light sensor, proximity sensor, gravity sensor

## PERFORMANCE

Processor Android 9: Qualcomm Snapdragon™ 450 Octa-core, 1.8 GHz

Android 11: Qualcomm Snapdragon™ 662 Octa-core, 2.0 Ghz

**RAM & ROM** 3 GB + 32 GB / 4 GB + 64 GB

Operating System Android 9/11
Support SDK Provided

Tool Eclipse / Android Studio

**Language** Java

**Expansion** Supports up to 128 GB Micro SD card

#### **ENVIRONMENTAL SPECIFICATION**

Temperature -20 °C to 50 °C (Operating)

-4490°C tto7700°C (\$\$00agg))

Humidity 5% RH to 95% RH

Sealing IP65

Tumble Specification 1000 x 0.5 m / 1.64 ft. falls

Drop Test Multiple 1.8 m / 5.9 ft. drops

### COMMUNICATION

Interface USB Type-C, USB 3.0, OTG, extended thimble

WLAN Support 802.11 a/b/g/n/ac/ax-ready/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4,IPV6, 5G PA

**WWAN** 2G, 3G & 4G

Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR Bluetooth 5.1

Vo-LTE Vo-LTE HD Video Voice call
GNSS GPS/AGPS, GLONASS, Galileo

#### **UHF RFID**

Frequency 865-868 MHZ

Protocol EPC C1 GEN2 / ISO18000-6C

Engine Impinj E710 / Impinj Indy R2000

Antenna Circular Polarized Antenna (4 dBi)

Power 1W (0 dBm to 30 dBm Adjustable) 2W (Optional)

R/W Range Up to 15 m (Tag & Environment Dependent)

**Reading Rate** 900+ tags/sec

#### **CAMERA**

Rear Camera Rear 13 MP Autofocus with flash

# OPTIONAL FEATURES

Barcode 1D & 2D

NFC ISO14443A/B

### **ACCESSORIES**

Standard Separate handle with one button, battery, Wrist Strap, Charging Cradle

## ORDER INFORMATION

Part Number IDT.RH.C61













Retail

Construction

ETC

Manufacturing

Transport

Supply Chain



