

SEMI AUTOMATIC TURNSTILE GATE IDT-T1000





No attrition & High-Temperature

Low Noise & High Resistant Intelligence

24 V DC Negligible Brushless Motor, Maintenance Low Noise

Failure-proof

Electromagnetic Solenoid Valve

IDT-T1000 (semi-automatic tripod turnstile) is driven by DC brushless motor, one can easily pass with veryless passing resistance. It has several working modes such as bi-direction, and single direction and all the modes can be set by using the buttons on the main control board. Beams will fall automatically when power is off and auto rise when power is on or auto stop on obstacles. It can also be integrated with function and face detection biometrics for no-touch use.

TECHNICAL SPECIFICATION

Model	IDT -T1000
Size	360mm x 260mm x 980mm
Material Structure	304 original brushed stainless steel, acrylic
Channel Width	510mm
Thickness	The full thickness of the outer box is $1.0 + 3.0$ mm
Traffic Speed	25-30 people/min in normal open mode and
	15-20 people/min in normally closed mode
Channel Width	One-way traffic/Two-way traffic
Opening Mode	ID/IC Card swiping and other reading head verification opening, button opening, etc.
Opening Signal	Dry contact signal
Life	≥5 million times
Power	30-60 Watt
Applicable Temperature	-20°C ~+75°C

Part No.

IDT.T1000

APPLICATION AREA



Residential



Health



Educational

Institute



Government



Defense



ID TECH SOLUTIONS PVT. LTD.

610, Udyog Vihar Phase-5, Gurgaon, Haryana - 122016, INDIA | T. : +91-124 - 4255530 (6 Lines) E.: info@idsolutionsindia.com | W: www.idsolutionsindia.com

The product specifications and descriptions listed in the specification sheet are subject to change anytime without notice. ©2023 ID Tech Solutions Pvt. Ltd. All Rights Reserved.

