

# UHF WINDSHIELD TAG IDT WT 03







Tamper Proof

IP 65

**UHF RFID** 



RFID UHF Windshield Tag IDT WT 03 is a passive tag that is designed to be attached to the windshield of vehicles. These tags are an essential part of parking automation as they are easy to use and offer a long reading range. They are also tamper-proof, ensuring that they cannot be removed or altered without authorization. With a reading range of up to 10m, these tags can be identified easily over a long distance, making them ideal for use in parking management systems. Additionally, the tags can be imprinted with customized information to meet the specific needs of different businesses.

#### PHYSICAL PARAMETERS

Dimensions	100mm x 50mm	
------------	--------------	--

Weight	$5g \pm 2$

Encasement / Material PET

Packaging Premium Plastic Packing

### **ENVIRONMENTAL SPECIFICATION**

Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Chemical Resistance	Resistant To Chemical Solvent and Moisture
Shock & Vibration	MIL STD 810-G

Attachment With 3M Adhesive


Sealing IP 65

#### **UHF PERFORMACE**

Working Frequency	865 – 868 MHz / 902 – 928 MHZ
Standard Protocol	ISO/IEC 18000-6C, EPC Global C1G2
Chip Type	Alien Higgs-3 /4, Monza 4/4QT/5/R6/R6P, UCODE 7/8 chip
FPC Memory	Chin Dependent

TID Memory	Chip Dependent
Read Range Fixed Reader	Up to 10 m (Reader & Chip Dependent)
Read Range Handheld Reader	Up to 5 m (Reader & Chip Dependent)

## TAG DIMENSION





#### **PERSONALIZATION**

Customer Specific Encoding of EPC **Pre-Encoding** 

Customer Specific Layout Including Logo, Text, Numbers, Barcode, etc. **Customized Printed** 

## ORDER INFORMATION

IDT.RF.T.WT03.BL (Blank) Part No.

IDT.RF.T.WT03.WP (With Print)



Toll Collection









Parking Automation

**Smart Cities** 

Public Transportation

Transportation



















